

1	2	3	4	5	6	7	8	9	10	11	12	13	14		
A	PIN-Belegung / <i>PIN Assignment</i>														A
B	CN1 CN2 A1 A12 B1 B12 A4 A9 B4 B9 A2 A3 A5 A6 A7 A8 A10 A11 B2 B3 B5 B6 B7 B8 B10 B11 A1 A12 B1 B12 A4 A9 B4 B9 A2 A3 A5 A6 A7 A8 A10 A11 B2 B3 B5 B6 B7 B8 B10 B11 SHELL SHELL				CN1 8.25±0.03 2.4±0.03 CE 6.65±0.2 21.0 12.3 40G/8K 240W goobay 8.34^{+0.06}_{-0.02} 2.56±0.04 CN2 8.0										B
C															C
D															D
E															E
F					USB-C™-Adapter vertikal 90° kurz, USB4™ - Sorgt für eine platzsparende Kabelführung - Hochwertiges, robustes Metallgehäuse - Kompatibel mit USB 3.1, USB 2.0, Thunderbolt™ 3 und Thunderbolt™ 4 Anschlüsse: Kontakte: Material Gehäuse: Max. Auflösung: Max. Datenübertragungsrate: Leistung: Isolationswiderstand: USB-C™-Buchse, USB-C™-Stecker vernickelt PINs: vergoldet Innen: PVC 45P, schwarz Außen: Aluminiumlegierung 8K @ 60 Hz 40 Gbit/s Max. 240 W (48 V ; 5A) 300 V/10ms $\equiv$, $\geq 10\text{ M}\Omega$ USB-C™ Adapter Vertical 90° Short, USB4™ - Ensures space-saving cable routing - High-quality, robust metal housing - Compatible with USB 3.1, USB 2.0 as well as Thunderbolt™ 3 and Thunderbolt™ 4 Connectors: Contacts: Material housing: Max. resolution: Max. data transmission rate: Power: Insulation resistance: USB-C™ socket USB-C™ plug nickel-plated PINs: gold plated Inside: PVC 45P, black Outside: Aluminium alloy 8K @ 60 Hz 40 Gbit/s Max. 240 W (48 V ; 5A) 300 V/10ms $\equiv$, $\geq 10\text{ M}\Omega$										F
G															G
H															H
I	Änderungen Datum Name gez.: 25.07.2024 alw gepr.: 25.07.2024 alw Norm: Änderungen vorbehalten / <i>Subject to change</i>				Bezeichnung USB-C 4.0 240W 40G 90° Adapter Breit Lang F-M Zeichnungs-Nr.: 74442								Blatt 1/1 von		I
J													J		
1	2	3	4	5	6	7	8	9	10	11	12	13	14		